
ALASKA 210 START





- Battery charger and maintainer with TRONIC technology for 12/24V lead batteries for motorbikes, cars, vans, etc.
- Automatic charge and maintenance in Tronic at 12/24V. 12V starting.
- Advanced charge and maintenance functions for EFB, AGM and low temperature.
- Digital display for voltage, current and charge percentage. Warning LED to indicate battery charge status and end of charge;
- Protection against overloads and polarity reversal.

TECHNICAL DATA

CODE	**807579**	CHARGE AND STARTING VOLTAG.	**12 / 24 V**	MIN.RATED REFERENCE CAPAC.	**10 / 10 Ah**
SINGLEPHASE MAINS VOLTAGE	**230 V**	EFFICIENT CHARGING CURRENT	**25 / 12 A**	MAX.RATED REFERENCE CAPAC.	**300 / 160 Ah**
MAINS FREQUENCY	**50 / 60 Hz**	RATED CHAR.CUR.EN60335-2-29	**15 / 8 A**	ADJUSTMENT POSITIONS	**5**
CHARGING ABSORBED POWER	**300 W**	START CUR.1V/C EN60335-2-29	**100 A**	DIMENSIONS (LxWxH)	**24,5 x 19,5 x13 cm**
STARTING ABSORBED POWER	**2,2 kW**	MAX STARTING CURRENT	**150 A**	WEIGHT	**7,57 kg**

DESCRIPTION

Electronic battery charger and maintainer with TRONIC technology for WET, GEL, AGM, MF, PbCa, EFB batteries at 12V/24V.
12V starter.
Advanced charging and maintenance functions for EFB, AGM and low temperature batteries.
Display for voltage, current, and charge percentage.
Features:

- Automatic charge and maintenance in Tronic at 12/24V;
- 12V starting;
- Advanced charging and maintenance functions for EFB, AGM and low temperature ;
- Digital display for voltage, current and charge percentage ;
- Warning LED to indicate battery charge status and end of charge;
- Protection against overloads and polarity reversal.

Complete with cable with clamps.

DOWNLOAD

CATALOG IMAGE

INSTRUCTION MANUAL

CERTIFICATE